

Caterina Lobefalo

Rockdelta

SPONSORED BY

AC
Ingenieros

VIBRATIONAL IMPACT OF URBAN RAIL INFRASTRUCTURES

Attenuation results with resilient stone wool mats

Caterina Lobefalo




TOPICS




1. Vibrational impact causes and effects
2. Stonewool resilient mitigations
3. Vibration transmission and modelling
4. Experimental results

RAILWAYS – A SOURCE OF VIBRATIONS



It has been proven that the best way of isolating vibrations is by acting at the source = The track


- Vibrations are inherent to all traditional railway systems due to the wheel and the rail interaction
- Vibrations can be transmitted through the ground and can be perceived as vibrations or re-radiated noise
- In contrast to audible sound, vibrations have the biggest impact at low frequencies (between 1 and 200 Hz)
- When not properly controlled, vibrations can lead to human discomfort, high precision equipment inaccuracy and in extreme cases, building masonry damage



RAILWAYS – A SOURCE OF VIBRATIONS



WHICH ELEMENTS OF THE SURROUNDING ENVIRONMENT INFLUENCE THE VIBRATIONS PATH?




ROCKDELTA SOLUTIONS – STONEWOOL MATS

Track design

- Mass
- Resilient elements



Rockdelta RB for ballasted tracks



Rockdelta RX for ballastless tracks

ROCKDELTA SOLUTIONS – STONEWOOL MATS



Vibro-acoustic capabilities

Effectively reduces vibration and noise



Water properties

Resistant to water



Robustness

Performs consistently under any conditions



Installation and storage

Efficient and simple



Fire resistance

Protects construction environment from fire



Aesthetics

Can be used with all track top finishes




Thermal properties

Insulates against frost heaves and heat loads



Circularity

Natural product for a circular economy



MOTIV is a semi-analytical model for predicting ground vibration from surface and underground trains, including the effects of the track structure, vehicle type and ground properties.

MOTIV also calculates the Insertion Loss and the expected rail deflection by the use of elastic elements in track.

PREDICTION MODELS

MOTIV GUI version 1 - University of Southampton & University of Cambridge

MOTIV version 1

Surface railway

Underground railway

EPSRC
Engineering and Physical Sciences
Research Council



UNIVERSITY OF Southampton UNIVERSITY OF CAMBRIDGE

MOTIV RELEASE NOTES

MOTIV software was developed in the ISVR (Institute of Sound and Vibration Research) within the EPSRC funded research project MOTIV: Modeling Train Induced Vibration (EP/K006002/1, EP/K005847/1, EP/K006655/1). MOTIV is a collaborative research project between ISVR at the University of Southampton and the Dynamics and Vibration Research Group (DVRG) at the University of Cambridge. For more details visit: <https://motivproject.co.uk>

The MOTIV software is a semi-analytical model developed for the prediction of

<https://motivproject.co.uk>



EXPERIMENTAL RESULTS: BREST TRAMWAY

The Brest tramway is located in Brest which is a port city of Brittany in north-western France.

It's a 14.3-kilometre line consisting of a 28-stop, two-branch.

Construction work on the platform began in early 2010 and the system began service on 23 June 2012.




VIBRATIONAL MEASUREMENTS

The purpose of the measurements which have been carried out is to validate the technical ability of RockDelta anti-vibration mats to achieve the required vibration attenuation.

The test area is located between PK 11090 and PK 12050 (route de Gouesnou, in BREST).

The tested section is equipped with RockDelta product type "RockXolid 50", thickness 50mm, with drainage channels.



VIBRATION MEASUREMENTS

To perform the measurements, the following equipment has been used:

- Impact hammer;
- 3 PCB2 accelerometers;
- 1 calibrator;
- 1 acquisition and processing system.

The quantity measured is the "transmission" loss.



The measurement method used first requires determining the transfer mobilities at the different points.

To do this, three sensors are used:



- sensor A: on the rail, in line with the excitation point;
- sensor B: on the floating slab, at the edge of the vertical joint;
- sensor C: outside the floating slab, at the edge of the vertical joint (close to point C);

In some cases, an additional sensor is also used:


- sensor D: outside the floating slab, 3m from the axis of the track (this point may, for practical reasons, in some cases has been impossible to measure)



VIBRATION ATTENUATION RESULTS



VIBRATION ATTENUATION RESULTS



The various results presented show that the transmission loss measured at the three or four selected sites complies with the usual requirements of project managers and track-laying companies, i.e. 20 dB minimum for third octaves above 50 Hz.

These results were obtained while the coating was absent, which is slightly detrimental.

Finally, the design of the test area, with integrated manholes, will make it possible to carry out the same tests with Rolling Stock and thus confirm the good results obtained.



Questions?



THANK YOU!

Caterina Lobefalo



caterina.lobefalo@lapinus.com

Sergio Colomer Marti



s.colomer@lapinus.com

Gaspar Acosta Flaque



gaspar@acosta-ing.com